G-TEL Enterprises, Inc. 16840 Clay Rd. #118 Houston, TX 77084 USA - Tel: 281-550-5592 Fax: 281-550-1028



G-Tel Inmate Phone Model# JP-3500

Armored Analog

Features:

- Constructed of durable 14-gauge stainless steel
- Built in mounting plate designed for fast, easy installation
- Mounting plate includes gasket which prevents moisture from entering phone
- Oversized line-wire entrance hole w/ moisture preventing gasket
- Mounts directly to the wall or installs inside a hood/enclosure
- Tamper resistant locking system
- Oversized stainless steel ADA keypad
- Adjustable volume button for full ADA compliance
- Magnetic, sealed Hookswitch
- Armored handset cord, with internal lanyard, is made to Bell Core standards and withstands minimum 1000 lb pulling test

G-Tel JP-3500 Technical Parameters:

Protection Class: **IP54** Ambient Temperature:

-40 ? ~ + 60 ? -40 F ~ + 140 F

Relative Humidity: ≤95% (at room temperature)

Atmospheric Pressure:

80 ~ 110KPa

Frequency Response:

250 ~ 3000 Hz

Supply Voltage: 48 ~ 60V

Feed Current: 25mA

Call Transfer Index:

SLR≤12 dB,

RLR≤-1dB, STMR≥10dB

Environmental Noise: ≤70dB

Ringing level: ≥80dB


Operates on C.O., analog lines or analog dialtone PABX/KSU stations

Dimensions:

11¼" tall, 5¼" wide, 6 "deep 287.5×135×75mm

Weight: 9lbs, 3KG

- Handset cord retaining bracket is designed for fast, easy handset changes
- Stainless steel grommet provides added security for the handset cord
- Adjustable handset cord lengths, comes standard with 24" Handset length
- Optional noise-canceling microphone available
- Large customizable instruction card area



G-TEL Enterprises, Inc. - Payphone.com 16840 Clay Rd. #118 Houston, TX 77084 gtel@payphone.com International: 281-550-5592 Toll Free: 1-800-884-4835

> Fax: 281-550-1028 www.payphone.com